

Claims

1. A syringe type ampoule having a) a barrel with a front end and a rear end defining an axis therebetween, the barrel having substantially constant cross-section between the front end and the rear end, at least the front end ending in an opening, b) a sealer attached to the front end and sealing the opening, c) at least one piston movably and sealingly arranged within the barrel and d) a sleeve extending along at least a part of the barrel, the sleeve having a front part and a rear part, the front part being connected to the sealer, characterized in the improvement comprising that the barrel has a front end terminating in an edge surrounding the opening, the edge having an outer circumference substantially equal to the barrel outer circumference.

2. The ampoule of claim 1, characterized in that the barrel is substantially cylindrical and that the edge and barrel outer circumferences are substantially circular.

3. The ampoule of claim 1, characterized in that the barrel cross-section is constant to a deviation of less than 2 mm, preferably less than 1 mm and most preferably less than 0.5 mm, when measured as maximum to minimum outer diameter or generally between diametrical points on the outer circumference.

4. The ampoule of claim 1, characterized in that the sealer at least somewhere extends outside the outer diameter of the front end outer diameter and the barrel outer diameter.

5. The ampoule of claim 1, characterized in that the barrel is of dual or multi chamber type incorporating at least one mixing arrangement between chambers.

6. The ampoule of claim 5, characterized in that the mixing arrangement is a non-sealing section for the piston distributed substantially around the barrel circumference.

7. The ampoule of claim 1, characterized in that the barrel has a rear end terminating in an rear edge surrounding a rear opening, the rear edge having an outer circumference substantially equal to the barrel outer circumference.

8. The ampoule of claim 1 or 7, characterized in that the edge is rounded.

9. The ampoule of claim 1 or 7, characterized in that substantially all edge material is kept within the barrel external circumference.

10. The ampoule of claim 1 or 7, characterized in that substantially all edge material is kept outside the barrel internal circumference.

11. The ampoule of claim 1, characterized in that the sealer has a part penetrating into the opening and having radial contact with the barrel interior surface.

12. The ampoule of claim 1, characterized in that the sealer has a flange part extension larger than the barrel circumference at the opening and/or larger than the barrel
5 largest circumference.

13. The ampoule of claim 12, characterized in that the extension is at least 0.05 mm, preferably at least 0,1 mm and most preferably at least 0,2 mm larger but smaller than 10 mm, preferably smaller than 5 mm and most preferably smaller than 2 mm.

14. The ampoule of claim 12, characterized in that the flange has said extension
10 sion around substantially its entire circumference.

15. The ampoule of claim 1, characterized in that the sealer is resilient.

16. The ampoule of claim 1, characterized in that the sleeve is attached to the barrel.

17. The ampoule of claim 16, characterized in that the attachment is made to
15 the rear part of the barrel.

18. The ampoule of claim 16, characterized in that the attachment comprises at least one structure extending radially inwards behind barrel rear end.

19. The ampoule of claim 1, characterized in that the sleeve front part is connected to the sealer by at least one structure extending radially inwards in front of a sealer
20 part.

20. The ampoule of claim 1, characterized in that the sleeve comprises auxiliary structures, such as structures selected from the group consisting of fastening structures, guiding structures, plunger and fingergrasp structures, dosing mechanism structures, needle attachment structures or combinations thereof.

21. A process for the manufacture of a prefilled syringe type ampoule having a) a barrel with a front end and a rear end defining an axis therebetween, the barrel having substantially constant cross-section between the front end and the rear end, at least the front end ending in an opening, b) a sealer attached to the front end and sealing the opening, c) at least one piston movably and sealingly arranged within the barrel and d) a sleeve extending along at
30 least a part of the barrel, the sleeve having a front part and a rear part, the front part being connected to the sealer, characterized in that the process comprises the steps of

inserting the piston through the front end opening to a distance from the opening into a sealing engagement with the barrel interior to form a chamber between the piston and the opening,

filling material into the chamber and

5 sealing the opening with the sealer.

22. The process of claim 21, characterized in that a lyophilizing step is performed before the sealing step.

23. The process of claim 21, characterized in that the sealing step includes the step of inserting a sealer part into the opening and contacting the part with the opening
10 interior surface.

24. The process of claim 21 or 23, characterized in connecting the sleeve to the sealer after the sealing step.

25. The process of claim 24, characterized in the step of securing the sleeve to the barrel rear end.

15 26. The process of claim 21, characterized in the step of inserting a second piston through the rear opening of the barrel.

27. The process of claim 21, characterized in the step of performing a filling operation through the rear opening before inserting the second piston.

28. A prefilled syringe type ampoule manufactured according to the process of any
20 one of claims 21 to 28.

29. A carrier/ampoule unit, for use in manufacture of prefilled ampoules, the unit comprising i) at least one ampoule and ii) a carrier having one or several seats for an ampoule, the seat providing a channel for axial insertion but radial retention of the ampoule, the ampoule comprising a) a container part with a front or upper end and a rear or lower end defining
25 the ampoule axis therebetween, defining the radial directions perpendicular to the axis and defining an ampoule height and b) an opening to the container part at least at the front end, characterized in the improvement comprising

that the channel is formed as a cavity,

that the cavity walls has at least the same height along the ampoule axis as the am-
30 poule height and

that the cavity walls are substantially continuous around said axis and along said height.

31. The unit of claim 30, characterized in that the container part is at least partly symmetrical with constant cross-section around a symmetry axis.

33. The unit of claim 29, characterized in that the ampoule comprises a syringe barrel having a front opening and a rear opening.

35. The unit of claim 33, characterized in that the barrel is a dual or multi chamber type having at least one valve or by-pass arrangement.

37. The unit of claim 29, characterized in that the channel width is about the same as ampoule largest width.

20 39. The unit of claim 29, characterized in that the channel has a length at
least corresponding to ampoule length.

41. The unit of claim 40, characterized in that the unit has a sealer arranged in the channel at the ampoule front end.

43. The unit of claim 29, characterized in that the seat comprises at least one lock attached to the carrier and able to restrict ampoule axial movement.

30 44. The unit of claim 43, characterized in that the lock has a surface extending into the channel at ampoule front and/or rear end.

45. The unit of claim 44, characterized in that the surface only partially covers the channel cross-section.

46. The unit of claim 45, characterized in that the surface only partially covers the ampoule end surface.

5 47. The unit of claim 43, characterized in that a single locking structure provide lock surfaces for more than one seat.

48. The unit of claim 47, characterized in that the locking surface comprises at least one bar or band spanning over more than one channel.

49. The unit of claim 43, characterized in that the lock is releasably attached
10 to the carrier.

50. The unit of claim 43, characterized in that the seat comprises two locks with a separation at least equal to ampoule height.

51. The unit of claim 50, characterized in that the separation is larger than the ampoule height.

15 52. The unit of claim 51, characterized in that the ampoule and a sealer are arranged between the locks.

53. The unit of claim 29, characterized in that it comprises a tool arranged axially movable in relation to at least one channel and having a part able to enter the channel.

54. The unit of claim 53, characterized in that the tool is arranged at least at
20 the carrier upper end.

55. The unit of claim 53, characterized in that the tool is used as lock.

56. The unit of claim 53, characterized in that the tool have several parts able to enter several channels at the axial movement.

57. The unit of claim 53, characterized in that the carrier has guiding structures for the tool axial movement.
25

58. The unit of claim 57, characterized in that each channel is provided with individual guiding structures.

59. The unit of claim 57, characterized in that the guiding structures comprises a stop surface for the tool axial movement towards the channel.

30 60. The unit of claim 57, characterized in that the guiding structures comprises recesses in the carrier body.

61. The unit of claim 60, characterized in that

62. The unit of claim 29, characterized in that the carrier comprises venting conduits at least between ampoule front end and the carrier exterior.

63. The unit of claim 62, characterized in that the conduits are formed as recesses in the carrier body.

5 64. A carrier/ampoule unit, for use in manufacture of prefilled ampoules, the unit comprising i) at least one ampoule and ii) a carrier having one or several seats for an ampoule, the seat providing a channel for axial insertion but radial retention of the ampoule, the ampoule comprising a) a container part with a front or upper end and a rear or lower end defining the ampoule axis therebetween, defining the radial directions perpendicular to the axis and
10 defining an ampoule height and b) an opening to the container part at least at the front end, characterized in the improvement comprising

that the channel length is longer than the ampoule height and

that the channel part beyond the ampoule comprises an interior surface distributed around the channel circumference.

15 65. The unit of claim 64, characterized in that the surface is generally tube shaped over at least an axial part.

66. The unit of claim 64, characterized in that the surface has substantially the same cross-section profile as the channel part occupied by the ampoule.

20 67. The unit of claim 64, characterized in that a sealer is arranged at the surface.

68. The unit of claim 67, characterized in that the sealer is frictionally held to the surface.

69. The unit of claim 67, characterized in that the sealer is positioned above the front opening of the ampoule.

25 70. The unit of claim 64, characterized in that the carrier has several channels and that each channel has said interior surface.

71. The unit of claim 64, characterized in any characteristic set forth in claims 29 to 63.

30 72. A carrier/ampoule unit, for use in manufacture of prefilled ampoules, the unit comprising i) at least one ampoule and ii) a carrier having one or several seats for an ampoule, the seat providing a channel for axial insertion but radial retention of the ampoule, the ampoule comprising a) a container part with a front or upper end and a rear or lower end defining

the ampoule axis therebetween, defining the radial directions perpendicular to the axis and defining an ampoule height and b) an opening to the container part at least at the front end, characterized in the improvement comprising

5 a lower lock surface attached to the channel and extending at least partially into the channel,

an upper lock surface attached to the channel and extending at least partially into the channel,

the upper lock surface and the lower lock surface being axially separated with a distance at least corresponding to the ampoule height and

10 at least one of the lower lock and the upper lock being releasably attached to the channel.

73. The unit of claim 72, characterized in that the lower lock and/or the upper lock are axially movably attached to the channel.

74. The unit of claim 72, characterized in any characteristic of claims 29 to 15 63.

75. A carrier/ampoule unit, for use in manufacture of prefilled ampoules, the unit comprising i) at least one ampoule and ii) a carrier having one or several seats for an ampoule, the seat providing a channel for axial insertion but radial retention of the ampoule, the ampoule comprising a) a container part with a front or upper end and a rear or lower end defining 20 the ampoule axis therebetween, defining the radial directions perpendicular to the axis and defining an ampoule height and b) an opening to the container part at least at the front end, characterized in the improvement comprising

several seats arranged in the carrier,

25 a lower lock surface attached to each channel and extending at least partially into the channel,

an upper lock surface attached to each channel and extending at least partially into the channel,

at least one of the lower lock and the upper lock being releasably attached to the channel and

30 guiding structures for at least the releasable lock arranged on the carrier at each channel.

76. The unit of claim 75, characterized in that at least the releasable lock is axially movable in relation to the channel.

77. The unit of claim 76, characterized in that the guiding structures comprising at least a stop surface limiting movement of the movable upper lock or lower lock towards
5 the channel.

78. The unit of claim 75, characterized in any of the characteristics of claims 29 to 63.

79. A method for the manufacture of prefilled ampoules by use of a carrier/ampoule unit, the unit comprising i) at least one ampoule and ii) a carrier having one or several seats
10 for an ampoule, the seat providing a channel for axial insertion but radial retention of the ampoule, the ampoule comprising a) a container part with a front or upper end and a rear or lower end defining the ampoule axis therebetween, defining the radial directions perpendicular to the axis and defining an ampoule height and b) an opening to the container part at least at the front end, characterized in the steps of

15 inserting an ampoule in a channel,
filling material into the ampoule
sealing the ampoule opening with a sealer and
removing the ampoule from the channel.

80. The method of claim 79, characterized in the steps of inserting the am-
20 poule through a first end of the channel and performing through the same end of the channel an additional operation selected from the group consisting of inserting a piston into the ampoule container, filling a substance into the ampoule container, evaporating a component from the container, inserting a sealer into the channel, removing the ampoule from the channel and combinations of these steps.

25 81. The method of claim 80, characterized in the step of keeping the first end upright under the inserting and filling steps.

82. The method of claim 80, characterized in that the first end is the upper carrier end.

83. The method of claim 80, characterized in the evaporating step comprises
30 a lyophilizing step.

84. The method of claim 80, characterized in the step of performing from a second end of the channel an additional step selected from said group.

98. The ampoule of claim 97, characterized in that the rear barrel end has a rear opening with a rounded edge having the material distribution stated.

100. The ampoule of claim 97, c h a r a c t e r i z e d i n that the barrel comprises one of a by-pass arrangement, a piston or combinations thereof.

102. The method of claim 101, characterized in that the heating is made by laser.